

ANTICORRay MASTIC FILLER

CORROSION PROTECTION MATERIALS

APPEARANCE



PRODUCT DESCRIPTION

Adhesive:

- Tape based on polyolefin copolymers.

Colour:

- Black.

TECHNICAL DATA

Parameter	Unit	Value
Density	kg/dm ³	1.6
Solubility in water	-	insoluble

Product holds the certificate of the DVGW Institute and building mark „B”.

Product is the element of system ANTICORRay REP for damage repair (according to EN 12068), contains the following components:

System A:

ANTICORRay Epoxy Primer,
ANTICORRay Mastic Filler,
ANTICORRay REP – repair patch.

System B:

ANTICORRay Mastic Filler, ANTICORRay REP – repair patch.

ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.

ANTICORRay MASTIC FILLER

Corrosion protection filling material of 3LPE coating resulting from mechanical damage reaching the steel surface.

APPLICATION

- Designed for deep damage repairs of the steel surface coatings.

FEATURES & ADVANTAGES

- Permanently plastic and manually mouldable (without heating).
- High adhesion to repair patch ANTICORRay REP.
- Ensures low cathodic disbondment.
- High electrical insulation parameters in the place of repair.

USAGE

- According to ANTICORRay REP technology.

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

PRODUCT FORM & SIZE AVAILABLE

Rolls: 40 mm x 2 m