

ANTICORRay MELT STICK

CORROSION PROTECTION MATERIALS

APPEARANCE



PRODUCT DESCRIPTION

Material

- Polymer flexible rod, hot melt adhesive.

Colour:

- Black.

ANTICORRay Melt Stick

Elastomeric filling material for repair of damaged surface of 3LPE coating.

APPLICATION

- For repairs of damaged surfaces of coatings.

FEATURES & ADVANTAGES

- High adhesion to 3LPE coatings.
- High resistance to mechanical damage (impacts, pressure).
- High dielectric strength.

USAGE

- According to ANTI-CORRay REP technology.

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: up to 25°C.

PRODUCT FORM & SIZE AVAILABLE

25 mm x 300 mm.

TECHNICAL DATA

Parameter	Unit	Value	Test method
Density	g/cm ³	0.96	ISO 1183
Hardness	Shore D	5	ISO 868
Solids content	%	100	-
Melt index			
125°C / 2.16 kg	g/10 min	14	ISO 1133
190°C / 2.16 kg		300	

Product holds the certificate of the DVGW Institute and building mark „B“.

Product is the element of system ANTI-CORRay REP for damage repairs (according to EN 12068).

ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.